



0101010
0010101
1010101
0101010

ردیاب کوچک



■ نصب ساده، ردیابی سریع، پایدار و قابل اعتماد.

این ردیاب‌ها با نصب آسان، طراحی فشرده و امکانات پایه‌ای ارتباطی، برای ناوگان‌هایی که به دنبال راه حل ساده، سریع و قابل اعتماد برای پایش موقعیت خودرو هستند، انتخابی منطقی و مقرون به‌صرفه به شمار می‌روند؛ چرا که بدون نیاز به تغییرات فنی در خودرو، امکان نظارت مستمر و مؤثر فراهم شده است.

ویژگی‌ها:

■ کوچک و سبک

■ دقت بالا در موقعیت یابی

■ نصب آسان و بدون نیاز به سیم کشی Plug & Play

■ پشتیبانی از هات اسپات داخلی برای اتصال هم‌زمان تا ۸ دستگاه

امکانات:

■ قابلیت تعریف حصار جغرافیایی

■ هشدار جدا شدن از وسیه نقلیه

■ ارسال هشدار از طریق پیامک و اینترنت

■ تشخیص رفتار پایه راننده (سرعت غیرمجاز، ترمز شدید و ...)

کاربردها:

■ خودروهای شخصی

■ خودروهای اجاره‌ای و اشتراکی

■ تاکسی‌ها و خدمات حمل و نقل شهری

■ تاکسی‌های اینترنتی



TC68L




TS299L





Category	Specification / Feature	TS299	TC68
Communication & Positioning	GSM	4G (LTE Cat 1/4), 3G, 2G	4G (LTE Cat 1/4/M1/NB2), 3G, 2G
	SOS Button	✓	✓
	Bluetooth	Optional	Bluetooth 4.2 and Bluetooth 5.0
	Wi-Fi Hotspot	Optional	2.4 GHz WiFi hotspot
	GNSS (GPS)	GPS/BeiDou/GLONASS	GPS/BeiDou/GLONASS
	LBS	✓	✓
Power and Battery	GPS Accuracy	2.5m	2.5m
	Power supply	DC 11.5–36 V / 1 A	DC 11.5–36 V / 1 A
	Power consumption	standby mode: 100 mA	standby mode: 100 mA
	Backup battery	(optional) 200 mAh/3.7 V	(optional) 200 mAh/3.7 V
	Charging	(a)Magnetic (b)Wireless	(a)Magnetic (b)Wireless
Device and Build	Working hour	Power-saving mode: 20 hours; Normal working mode: 2 hour	Power-saving mode: 20 hours; Normal working mode: 2 hour
	Dimensions	105 mm x 51 mm x 23.5 mm	67 mm x 51 mm x 23.5 mm
	Weight	60g	60g
	Operating Temperature	-20°C~55°C	-20°C~55°C
	Operating Humidity	5% to 95%	5% to 95%
	Memory	8 MB buffer	8 MB buffer
	Certification	CE, ESD, ISO 7637	CE, CITEC
	OBD data	NO	✓
	LED Indicators	GSM LED indicator	GSM LED indicator
		GPS LED indicator	GPS LED indicator



DNM Telematics

✉ Info@dnm.co.ir

📧 @dnmcompany

🐦 @dnmcompany



Scan For More Information